

OFFICE OF THE PRINCIPAL BARUNESWAR MOHAVIDYALAYA

P.O-AREI, DIST-JAJPUR

Email: baruneswar college@gmail.com

web: www.baruneswarmohavidyalaya.com

QUOTATION CALL NOTICE

Sealed quotations are invited from registered firms having IT,PAN, & Up to date GST Registration according to OGFR-2023 guideline for procurement & installation of IT materials such as computers, UPS,MFM,LED TV, Wireless Mike camera etc. Firms should send quotations as per the specification given in college website www.baruneswarmohavidyalaya.com & website of Jajpur district www.jajpur.odisha.gov.in latest by 4.30pm 07.06.2025 . Firms are requested to write their contact details on the top of the envelop.

Principal-cum-Secretary
Principal-cum-Secretary
Paracipal
Barageswam/Alphayjdyalaya
Paraci Distrajour

Terms & Condition

- Bidder should submit Copy of Bid Specific OEM Authorization Certificate (MAF)/Certificate with OEM details such as name, designation, address.
- Bidder should have office in Odisha for better sales & services.
- Odisha GST mandatory for better sales & services.
- Bidder must submit last 3 year IT return.
- Bidder must have ISO 9001 certification for Quality management standards and CE Certification.
- Bidder must have MSME UDYAM Regd. Certificate.
- Bidders should submit the affidavit regarding none blacklisted from any Central/State/ PSU Organization in Non-Judicial one hundred stamp paper executed before Notary.
- All products should be of reputed brands.
- Bidder should supply and install the item in the concerned College.
- OEM must provide declaration about onsite warranty as per the tender terms.
- Bidder has to provide warranty period declaration on the letter head of OEM signed by Local Business Manager.
- All the required documents must be submitted as per Bid requirement, failing to which the bidder will be Rejected.
- EXPERIENCE: The bidder should submit the copy of the work order / completion certificate of contracts from any Govt. Department during last 03 financial years.

PRINCIPAL Baruneswar Mohavidyalaya
Po-Arei Dist-Jajpur

Quantities and Specifications of IT items to be purchased

Sl.No	Non-Govt. Aided College	Nos of College	Amount to be released (in lakhs)		Total Amount (il lakhs)
	No of No Govt. Aided Colleges having student's strength more than 750		8	1.I3 and above Desktop @50000*12=6 Lakh 2. UPS@3000*12=36000 lakh 3. MFM Printer@30000 *2=60000 4.1 LED Tv (65 inch) @0.70= 70000 5. Wireless mice &Camera for Virtual meeting = 25000 6. Internet Facility:-20,000/- Total=8.11 Lakh	1592
Aid hav stre	of Non-Govt. ed Colleges ing student's ngth less	449		1.I3 and above Desktop @50000*6=3.0 Lakh 2. UPS@3000*6=18000 t 3. MFM Printer@30000*2=0.60 Lakh 4.1 LED Tv(65 inch)@70000=.70 Lakh 5.Wire less Mice & Camera with MIC for Virtual meeting = 25000 6. Internet facility=20000 Total =4.93 Lakh	2020.5
		648			3612.5

Items	specification Specification	
Cabinet Form Factor	Tower/Micro Tower (15.1 to 26 Litres)	
Chipset Number	Intel H670/Intel® H770 or higher Chipset	
Processor Make		
Processor	Intel	
Processor Generation	x86 64-bit architecture	
Processor Description	13 Or higher	
Processor Number	Intel Core i3 or higher	
Number of Cores and Threads per Processor	Intel Core i3 13100 or higher Max Turbo Frequency 4.5Ghz, Minimum 4 Cores and 8	
Operating System	Threads or higher	
RAM Size (GB)	Windows 11 Home Factory Preloaded	
RAM Expandability up to (using spare DIMM Slots in GB)	DDR-4 8GB 3200 (16 X1) or higher (2 DIIM Slots)	
Integrated Graphics	64 GB or higher	
Supported for discrete NVIDIA/AMD Graphics Card up to 6GB	Intel UHD Graphics 770 or higher Yes	
Type of Drives used to populate the Internal Bays	NVMe SSD	
Total HDD Capacity (GB)	NA NA	
Total SSD Capacity (GB)		
Optical Drive	512GB NVMe SSD	
Drive Bays	Optional	
Slots for Upgradation	Two 3.5" (2.5") HDD 1 PCI Express 4.0 x16, 1 PCI Express 3.0 x1, 1 PCI (Full Height),	
LAN	2 M.2 slots for WLAN & SSD	
Ports and Connectors	LAN: Integrated 10/100/1000M Front: 1 headphone/microphone combo; 3 Super Speed USB 5Gbps signalling rate; 2 SuperSpeed USB 10 Gbps signalling rate; 1 USB Type-C, total 6nos USB in front for easy access Rear: 1 HDMI; 1 Serial Port; 1 line in; 1 line out; 1 power connector; 1 RJ-45; 1 DP; 2 USB 2.0	
Firmware Trusted Platform Module	TPM 2.0	
Hardware Security lock slot	Security lock slot	
Power Supply	180-260Watt Internal power supply with minimum 90% efficiency	
	Bidder should submit OEM bid specific authorization & the same authorization may be verified by the respective OEM i required.	
	OEM must have the ISO 9001,14001, ISO 20001, ISO 27001 Certificate	
Certification	Microsoft Windows, Energy star 8.0 certified	
	Bidder should submit BIS, BEE, EPEAT, UL, RoHS Certificate of products at the time of participation of the Bid.	
Keyboard Mouse	USB Keyboard; USB Optical Mouse	
Monitor	19.5" LED Display with CTO Certified and same must be belongs to the same OEM	
Years of Warranty	3 Year Onsite Warranty	

	600 VA Line Int	eractive UPS Specifications	
SI. No.	Feature	General Specifications	
1	UPS Capacity (total)	600VA/360W	
2	Input Voltage	230 VAC nominal	
3	Input Frequency	45 - 65 Hz	
4	Brownout Transfer	145 VAC typical	
5	Over-voltage Transfer	290 VAC typical	
6	Voltage on Battery	230 VAC typical (stepped approximated sine wave)	
7	Frequency – On Battery	SOHz typical	
8	Transfer Time	@50 Hz : 6 ms typical, 10 ms max	
9	Air Ventilation	Should have Side and Back Honey bee Perforation for headispersion UPS Should have conformal paint coating on PCB for Insulation for Dust and Humidity UPS Should have Battery Saver Option to increase the life of the Battery upto 5 years	
10	Protection from Humidity & Dust		
11	Battery Saver Option		
12	No Load Shutdown	UPS Should work on loads of 2-3 watts also	
		Full time, 160 joules	
13	AC Surge Protection		
14	Automatic Re start of UPS	In case the UPS backup is totally drained and switched off, when the grid power resumes the UPS Should Auto Start without human interference.	
	Type (maintenance-free)	12V, 7.2 Ah	
15	Typical recharge time	4-6 hours	
16	Operating Temperature	0°C to 40°C	
17	Storage Temperature	-15°C to 45°C	
18	3 power outlets	With battery backup and surge protection	
		1.2 meters	
20	Power Cord	27 min (normal mode)	
21	Runtime for Single PC load (60W ± 15W)	13 min (normal mode)	
22	Runtime for Workstation PC (100W ±15W)	Thru toggle button on front panel	
	Battery Saver (to save on battery life)	BIS	
24	Certification	Yes	
	Designed and Manufactured in India	2 years	
	Warranty		

Description of Stores	Generic	
0.03	Multifunction Machine Printer with Minimum 1 Year On Site	
	Warranty, including Cartridge and Power Cord/Adapter	
Core Function	The Control of Cartridge and Power Cord/Adapter	
Phot Took		
Carumon Tart	Print, Scan and Copy Laser	
Type of Printing		
RAM D	Composite Cartridge	
RAM Size (MB)	Monochrome (Black)	
Storage Capacity (in GB)	256	
	0	
Features		
Operating System Compatibility	Fax	
System Compatibility		
	Windows 10 and Above, Linux, Mac OS, Windows Server	
Print D.		
Print Paper Size	Printing	
Minimum Print Speed per	A4 and Legal	
	26 to 30	
(in PPM) (Black)		
Minimum Point 8		
Minimum Print Speed per	Not Applicable	
WILLIAM BS DOLISOVED 34201	The repullicable	
A4 Size-Colour (in PPM)		
Minimum Speed per Minute as		
per ISO/IEC 24734 in A3 Size-	Not Applicable	
Mono (in PPM)		
(III FFM)		
Minima		
Minimum Speed per Minute as	Not Applicable	
per 150/1EC 24734 in A3 Size		
Color (in PPM)		
Auto Duplevino Printing		
Auto Duplexing Printing/Coping (2-sided Feature)	Yes	
(# Sided Feature)		
Maximum Soc. 4	Scanning	
Maximum Scan Area	A4 and Legal	
(Platen/Flatbed Size)		
A4 Scan Speed -Colour (Image	11 to 20	
Per Minute) @ 300 x 300 dpi		
, С === л ооо арг		
Scan To Functions		
	Email	
A4 Scan Speed - Mono (Image	11 to 20	
Per Minute) @ 300 x 300 dpi		
	COPYING	
Reduction and Enlargement	Yes	

	PAPED HANDI W
Original	PAPER HANDLING
Original Document Feeder Type (For Scanning and Const.)	
(For Scanning and Copying)	Automatic Document Feeders (ADF)
Feeder Capacity (Number of Sheets) (For See	
Sheets) (For Seen in Minister of	31 to 40
Sheets) (For Scanning and Copying)	
Number of Main Paper Tray	
or Wall Paper Tray	1
Total Paper Tray Combined	
Capacity (Number) at 75 GSM	101 to 200
(Number) at 75 GSM	
Bypass Tray Facility	No
If Yes, Bypass Tray Capacity	0
Supacity	U
Connectivity	
Connectivity	LICO De 4 E''
Accessories Provided	USB Port,Ethernet Port,Wi-Fi
· · · · · · · · · · · · · · · · · ·	USB Cable
Minimum Yield of the	Performance
Cartridge/Ink/Toner supplied	700
with Machine as per IS/ISO/IEC:	
19752/2017 for Plants (A)	
19752/2017 for Black (Number of Prints)	
of Films)	
Minimum Yield of the	
Cartridge/Ink/Toner Supplied	0
with Machine as per IS/ISO/IEC:	
19798:2017 for Curr Volley	
19798:2017 for Cyan, Yellow	
and Magenta Color (Number of Prints)	
Films)	
Minimum Duty Ocale (1)	
Minimum Duty Cycle (Number of Prints/Month)	10,001 to 20,000
or randomonary	
	POWER
Power Supply	Single Phase AC 220 - 240 V, 50 - 60 Hz
Maximum Power Consumption	1300
(in Watt)	
Environmental	
Minimum Operating	10
Temperature (Degree C)	
Maximum Operating	30
Temperature (Degree C)	
· · · · · · · · · · · · · · · · · · ·	

Minimum Operating Humidity (%RH)	20
Maximum Operating Humidity (%RH)	80
	Dimension
Standard Machine Weight with Single Tray (in Kg)	11
	Certification
BIS CRS Compliance	Yes as per IS 13252 (Part 1)
Maximum Number of Prints covered under Product warranty (Whichever is earlier)	30000
EPR Registration in respect of the manufacturer/authorised importer as per E waste rules as amended up to date	Yes
Agreed to Provide a copy of EPR Registration Certificate to the Buyer on Demand	Yes

	Screen Size	65
	Brightness (cd/m²) Contrast Ratio	350Nits or better
Generals		1200:1
General Features	Dynamic Contrast Ratio	400,000:1
	Response Time (ms)	8.0
	Display resolution (H x V, pixels)	3840 x 2160
	HDR (High Dynamic Range) compatibility	Yes (HDR10, HLG)
	Aspect Ratio	16:9
	Portrait/Tilt Compatibility	Yes
	Dimming type	Frame Dimming
	Display Device	LCD
	Panel Type	IPS
Display features	Backlight type	Direct LED
	Color gamut (NTSC)	69%
	Operation time	16/7
-	Haze (%)	1 %
	Viewing Angle (Right/Left)	178 (89/89) degree
THE RESIDENCE OF THE PARTY SERVICE.	Viewing Angle (Up/Down)	178 (89/89) degree
	HDMI Signal	4096 x 2160p (24, 50, 60 Hz) 3840 x 2160p (24, 25, 30, 50) 60 Hz), 1080p (30, 50, 60 Hz) 1080/24p, 1080i (50, 60 Hz), 720p (30, 50, 60 Hz), 720/24p, 576p, 576i 480p,480i
Audio Specs	Speaker Position	Down Firing
	Audio Power Output	10W + 10W
Professional	Pro settings	Yes (Simple Pro settings men
features	HDMI auto wake-up	Yes
	Operating System	Android TV
	On-board Storage (GB)	16GB
	RAM	3GB
January Farm	Wi-Fi Certified	Yes
Network Specs	Wireless LAN	Integrated
	USB playback codecs	MPEG1:MPEG1/MPEG2 PS:MPEG2/MPEG2 WEBM:AV1/AC4/ogg/AAC
Convenience	On Screen Clock	Yes
features	Sleep Timer	Yes
	On/Off Timer	Yes
	Chromecast built-in	Yes
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Apple AirPlay	Yes
	IP Control	Yes
Control Cones	20012 A 15 2013 A 15 3 A 15 A 15 A 15 A 15 A 15 A 15	
ontrol Specs	RS-232C Control	Yes
	HDMI-CEC	Yes HDCP2.3 (for HDMI1/2/3)
	HDCP	

nputs and outputs	HDMI inputs total	3 (3Side)
	Analog Audio Input (s) (Total)	1 (Side Analog Conversion)
	Digital Audio Output (s)	1 (Side)
	USB ports	2 (Side)
Design features	Ethernet Inputs	1 (Side)
oesiku teatute?	VESA® Hole Pitch (W x H)	300 x 300 mm
	Rated Power Consumption	226W
Environment Specs	Power Consumption (in Standby)	0.5 W
	Dynamic Backlight Control	Yes
	Power Saving Mode / Back Light Off Mode	Yes
	Dimension of TV without Stand (W x H x D)	1462 x 842 x 71 mm
Measurements	Dimension of TV with Stand (W x H x D)	1462 x 912 x 338 mm
	Dimension of Package Carton (W x H x D)	1588 x 965 x 184 mm
	Weight of TV without Stand	20,4 kg
Weight	Weight of TV with Stand	21.3 kg
	Weight of Package Carton (Gross)	28 kg

lesy and Paincipal Paincipal Barungswar Mohavidyalaya Po-Arei, Dist-Jajpur